



Designation	LED Recessed Panel
Article No	3234042U09040DN
Frame	Aluminum
Colour	White
Optical Cover	PC micro-prismatic
Beam Angle	90°
Installation	Ceiling Mounting
Operating Temperature	-20° - +40°
Intelligent Control	DALI
Glare Reduction	UGR <19
Index of Protection	Schutzart
Protection Class	Schutzklasse
Certificates	Zertifikate
Height	Höhe
Length	Länge
Width	Breite
Gross Weight	Bruttogewicht
Light Source	Lichtquelle
LED Typology	LED Typologie
LED Quantity	LED Anzahl
Wattage	Lampenleistung
Light Output	Lichtemission
Luminous Flux	Lampenlichtstrom
Luminous Efficacy	Lichtausbeute
Light Colour Temperature	Lichtfarbe
SDCM	SDCM
Colour Rendering Index	Farbwiedergabeindex
Glare	Blendung
Life Span	Nutzlebensdauer
Power Supply	Betriebsgerät
Input Voltage	Eingangsspannung
Frequency	Frequenz
Power Factor	Leistungsfaktor
Dimming Technology	Dimmtechnik

Bezeichnung	LED Einlegeleuchte
Artikel Nr	3234042U09040DN
Rahmen	Aluminium
Farbe	Weiß
Optische Abdeckung	PC microprismatisch
Lichtaustrittswinkel	90°
Befestigung	Deckenauflage
Betriebstemperatur	-20° - +40°
Steuerungstechnik	DALI
Entblendung	UGR <19
IP20	
II	
CE, RoHS	
8 mm ultra-flat	
620 mm	
620 mm	
3,4 Kg	
LED	
Osram 4014	
154	
25W - 42W	
flicker-free	
5450 lm	
130 lm/W	
4000 K	
<5	
Ra 85	
UGR<19	
50000 h	
Dip Switch: 25W-42W	
200-240V	
50 / 60 Hz	
> 0,95	
None	